



**Catalog Number** 11322  
**UPC Number** 60198611322  
**Description** Nylon Insulated Ring Terminals  
 22-16 AWG




**Features**

- Color Coded insulation for easy identification
- Manufactured from high strength copper alloy
- Electro-tin plated for corrosion resistance
- Expanded Insulation funnel entry eliminates strand “Hang Up”, increases the crimping rates and the reliability of the termination
- Wire range stamped on the surface for easy interpretation
- Brazed seam prevent splitting under maximum pressure
- Serrated barrel & flared position of sleeve provides excellent contact & mechanical stress relief at insulation & barrel junction

**General**

**Insulation Type** Nylon  
**Material** Copper  
**Finish** Electro-tin plated  
**Color** Red  
**Wire Range** 22-16 AWG  
**Stud Size** 5/16



**Dimension Information**

L Inches (mm) 1.094  
 W Inches (mm) 0.457  
 D Inches (mm) 0.157  
 d1 Inches (mm) 0.067  
 d2 Inches (mm) 0.331  
 E Inches (mm) 0.433  
 F Inches (mm) 0.433  
 T Inches (mm) 0.03

**Specifications**

Temperature Rating 105°C  
 Voltage Rating 600 V  
 Flammability Rating UL94V-O  
 Amp Rating 22 AWG 9 Amps  
 20 AWG 12 Amps  
 18 AWG 17 Amps  
 16 AWG 18 Amps

**Packaging**

Bag Qty 100  
 Master Bag Qty 1000

**Certifications**

UL Yes  
 cUL Yes  
 RoHS Yes

