



Catalog Number 68312
UPC Number 6019868312
Description Cold Seal Cold Shrink Tubing



Features

- Cold Applied Cold Seal Shrink Tubing Technology
- Submersible Rated for Cable Jacket Repair & Splicing
- Conforms to ANSI C119.1 1986
- Silicone Rubber Jacketing Material
- Durable Tear Resistant Removable Rip-Cord Core
- 1000V Rated for Primary Insulation
- UV Resistant

General

Material: Silicone Based Rubber
 Corrugated Thermoplastic Removable Inner Core

Dimension Information

See Table

Specifications

Temperature Rating: -55 to 135°C
 Dielectric Strength: 28kV/mm
 Insulation Resistance: 700V/mil @ 500V
 1min DC voltage: 5.70x10¹⁰ ohm
 Volume Resistivity at 500V: 6.98x10¹³ ohm-cm
 Shrink ratio: >2:1

Packaging

Bag Qty 1

Certifications

ANSI C119.1 Compliant

Cat. No.	Conductor Range	Application Range	Length	Voltage	Bag Qty	Case Qty
68302	#2 - 1/0	0.37" - 0.57"	8"	1000	1	10
68304	2/0 - 400	0.57" - 1.35"	9"	1000	1	10
68306	500 - 800	0.97" - 1.95"	9"	1000	1	10
68308	500 - 800	0.97" - 1.95"	12"	1000	1	10
68310	900 - 1000	1.32" - 2.65"	9"	1000	1	10
68312	1250 - 2000	1.63" - 3.67"	9"	1000	1	10