



Catalog Number See Table  
 UPC Number  
 Description Copper Split Bolt  
 #8 Thru 750  
 UL467 DB Listed




**Features**

- Manufactured from High Strength High Conductivity Copper Alloy
- UL 467 Listed for Direct Burial and Grounding/Bonding Copper and CopperWekd Stranded Cable Only
- Conductor Spacer to accommodate dissimilar conductors

**General**

Conductor Size: #8 to 750  
 Material: Body: High Strength Electrolytic Copper  
 Nut and Spacer: Copper Alloy



**Dimension Information**

Stock Thickness See Table

**Specifications**

Temperature Rating 75° C  
 Voltage Rating 600  
 Flammability Rating N/A  
 Amp Rating To Conductor

**Packaging**

Box Qty See Table

**Certifications**

UL UL 467 Listed For Direct Burial  
 CSA Yes  
 RoHS N/A

Cat No.	AWG	Max Run To Max Tap	Min Run To Min Tap	Max Run To Min Tap	Min Equal Tap & Run	Torque In-Lb	B	C	L	R	V	W	Box Qty	Each
90314	8	8-8	10-16	8-16	10-10	88	0.472	0.562	0.854	0.413	0.145	0.65	100	
90316	6	4-4	8-14	4-14	8-8	165	0.492	0.625	0.906	0.413	0.165	0.722	100	
90318	4	4-4	6-14	4-14	8-8	165	0.709	0.812	1.16	0.579	0.268	0.938	50	
90320	2	2-2	6-14	2-14	6-6	275	0.748	0.812	1.26	0.614	0.326	0.938	50	
90322	1/0	1/0-1/0	2-14	1/0-14	4-4	385	0.787	0.937	1.54	0.708	0.374	1.08	50	
90324	2/0	2/0-2/0	1-14	2/0-14	2-2	385	0.866	1.06	1.69	0.807	0.421	1.28	25	
90326	3/0	3/0-3/0	2/0-8	3/0-8	1-1	500	1.1	1.25	2.09	0.976	0.531	1.45	25	
90328	4/0-250	250-250	4/0-8	250-8	1-1	500	1.1	1.25	2.09	1.06	0.579	1.45	25	
90330	350	350-350	350-1/0	350-1/0	2/0-2/0	650	1.22	1.5	2.36	1.18	0.7	1.73	12	
90332	500	500-500	500-2/0	500-2/0	300-300	825	1.34	1.75	2.84	1.34	0.815	2.1	12	
90334	750	750-750	750-4/0	750-4/0	750-750	1000	1.94	2.13	3.77	1.93	1.18	2.39	1	