



Catalog Number See Table
UPC Number
Description 3" Service Entrance Splices

Features

- Manufactured from High Strength High Conductivity Aluminum Alloy
- Color Coded Nylon Insulation Sleeves
- Oxide Inhibitor Coating
- CU/Al Rated
- Chamfered Barrel with Center Stop

General



Material: Aluminum Alloy
 Heat Stabilized Nylon Insulating Sleeve
Wire Range: #6 awg - 1 /0

Dimension Information

Length: 2-25/32"

Specifications

Temperature Rating:
Voltage Rating: 600
Flammability Rating: N/A
Amp Rating: To Conductor

Packaging

Box Qty See Table

Certifications

ANSI C119.4 Class A-3

UL
 cUL
 RoHS

		CONDUCTOR A				CONDUCTOR B				
		AL OR CU				AL OR CU				
Cat No.	Model	Color	Sol	Str	ACSR	Color	Sol	Str	ACSR	Box Qty
90672	UYR 02 D	Yellow		1/0	1/0	Red		1&2	2	100
90680	URR 22 D	Red		1&2	2	Red		1&2	2	100
90684	URB 26 D	Red		1&2	2	Blue	4	6	6	100
90688	UOO 44 D	Orange	2	4	4	Orange	2	4	4	100
90690	UOB 46 D	Orange	2	4	4	Blue	4	6	6	100
90694	UBB 66 D	Blue	4	6	6	Blue	4	6	6	100

www.morrisproducts.com

Morris Products 53 Carey Road, Queensbury, NY 12804