




Catalog Number See Table
UPC Number
Description Two Conductor One Hole Aluminum Mechanical Lug



Features

- Manufactured from High Strength High Conductivity Aluminum Alloy
- Electro-Tin Plated
- CU-AL Dual rated for AL/AL, AL/CU, CU/CU Applications
- Two Conductor Configuration

General

Conductor Size: See Table
Material: 6061-T6 Aluminum Alloy
Finish: Electro-Tin Plating
Screw Type: #14 Thru 1000 MCM

Dimension Information

See Table

Specifications

Temperature Rating 90° C
Voltage Rating 600
Flammability Rating N/A
Amp Rating To Conductor

Packaging

Box Qty See Table

Certifications

UL UL 486B UL41968 CU9AL Dual Rated
CSA LR27194
RoHS Yes

Cat No.	AWG	Fig.	Wire Range	Box Qty	L	W	H	Bolt	
TWO CONDUCTORS - ONE HOLE MOUNT									
90812	Jan-00	5	1/0STR. - 14SQL.	25	1.34	1.12	0.69	0.28	
90814	Feb-00	5	2/0STR. - 14SQL.	12	1.47	1.19	0.75	0.28	
90816	300	5	300MCM - 6SQL.	8	1.94	1.72	1	0.41	
90818	350	5	350MCM - 6SQL.	6	2.12	1.88	1.09	0.56	
90820	600	5	600MCM - 2SQL.	3	3.19	2.41	1.56	0.56	
90822	750	5	750MCM - 300MCM	3	3.38	2.93	1.94	0.66	
90824	1000	5	1000MCM - 350MCM	3	3.5	3.5	1.94	0.66	

www.morrisproducts.com

Morris Products 53 Carey Road, Queensbury, NY 12804