



Catalog Number See Table
UPC Number
Description Four Conductor Four Hole Mount Aluminum Mechanical Lug

- Features**
- Manufactured from High Strength High Conductivity Aluminum Alloy
 - Electro-Tin Plated
 - CU-AL Dual rated for AL/AL, AL/CU, CU/CU Applications
 - Two Conductor Two Hole or Four Hole Configuration

General
Conductor Size: See Table
Material: 6061-T6 Aluminum Alloy
Finish: Electro-Tin Plating
Screw Type: Hex Head
Wire Range: 300 Thru 1000 MCM

Dimension Information
 See Table

Specifications
Temperature Rating 90° C
Voltage Rating 600
Flammability Rating N/A
Amp Rating To Conductor

Packaging
Box Qty See Table

Certifications
 UL UL 486B UL 41968 CU9AL Dual Rated
 CSA LR 27194
 RoHS Yes

Cat No.	AWG	Fig.	Wire Range	Box Qty	L	W	H	Bolt
FOUR CONDUCTORS - FOUR HOLE MOUNT								
90872	300	8	250MCM - 6SCL	1	4.5	3.94	1.12	0.56
90874	350	8	350MCM - 6SCL	1	4.5	3.94	1.12	0.56
90876	600	8	600MCM - 4SCL	1	4.63	5	1.56	0.56
90878	750	8	800MCM - 300MCM	1	4.75	5.94	1.75	0.56
90880	1000	8	1000MCM - 500MCM	1	4.75	5.94	1.75	0.56