



Catalog Number See Table
UPC Number
Description Three Conductor Vertical Stacked Aluminum Mechanical Lug
 Two Mounting Holes




- Features**
- Manufactured from High Strength High Conductivity Aluminum Alloy
 - Electro-Tin Plated
 - CU-AL Dual rated for AL/AL, AL/CU, CU/CU Applications
 - Two Conductor Two Hole Configuration - Stacked

General

Material: 6061-T6 Aluminum Alloy
 Finish: Electro-Tin Plating
 Screw Type: Hex Head
 Wire Range: 3/0 - 750 MCM

Dimension Information
 See Table



Specifications

Temperature Rating 90° C
 Voltage Rating 600
 Flammability Rating N/A
 Amp Rating To Conductor

Packaging
 Box Qty See Table

Certifications

UL UL 486B UL 41968 CU9AL Dual Rated
 CSA LR 27194
 RoHS Yes

Cat. No.	AWG	Wire Range	Box Qty	L	W	H	Hole Space	Bolt	
PANELBOARD LUGS - 3 CONDUCTORS									
90918	600	600MCM - 3/0STR.	1	4.94	2.5	3	1.38	0.41	
90920	750	750MCM - 3/0STR.	1	4.94	2.63	3	1.38	0.41	