




Catalog Number See Table
UPC Number
Description Four Conductor Four Hole Mount Aluminum Mechanical Lug



Features

- Manufactured from High Strength High Conductivity Aluminum Alloy
- Electro-Tin Plated
- CU-AL Dual rated for AL/AL, AL/CU, CU/CU Applications
- Four Conductor Four Mounting Hole Configuration
2 Set Screws Per Conductor

General

Conductor Size: See Table
Material: 6061-T6 Aluminum Alloy
Finish: Electro-Tin Plating
Screw Type: 2 - Hex Head Screws Per Conductor
Wire Range: #6 - 600 MCM

Dimension Information
See Table

Specifications

Temperature Rating 90° C
Voltage Rating 600
Flammability Rating N/A
Amp Rating To Conductor

Packaging
Box Qty See Table

Certifications

UL UL 486B UL41968 CU9AL Dual Rated
CSA LR 27194
RoHS Yes

Cat. No.	AWG	Fig.	Wire Range	Box Qty	L	W	H	Bolt
FOUR CONDUCTORS - FOUR HOLE MOUNT								
90964	250	13	250MCM - 6SOL.	1	5.38	4.2	1.19	0.56
90966	600	13	600MCM - 4SOL.	1	5.19	5.28	1.56	0.56