



Catalog Number See Table  
 UPC Number  
 Description Bi-Metallic Pin Terminals  
 Solid Copper Pin  
 Offset

#### Features

- Manufactured from High Strength High Conductivity Aluminum Alloy
- Electro Tin Plated
- AL9CU Rated for Copper or Aluminum Conductors
- Oxide Inhibitor Coated Barrel
- EDPM Rubber Insulating Cover



#### General

Material: Aluminum Alloy  
 EDPM Rubber Insulating Cover  
 Wire Range: Conductor Size Pin Size  
 #6 #4  
 Thru 750 MCM Thru 500 MCM

#### Dimension Information

Length: See Table

#### Specifications

Temperature Rating: N/A  
 Voltage Rating: 600  
 Flammability Rating: N/A  
 Amp Rating: To Conductor

#### Packaging

Box Qty See Table

#### Certifications

UL Yes  
 cUL Yes  
 RoHS Yes

Cat. No.	Wire Size	Pin Size	O.D.	I.D.	Pin Dia.	Total Length	Pin Length	Body Length	Color Code	Inner Box	Outer Box
90985	2/0	1	0.85	0.44	0.33	2.69	1.12	1.57	White	10	100
90986	3/0	1/0	0.85	0.5	0.37	2.8	1.25	1.55	White	10	100
90987	4/0	2/0	0.85	0.547	0.42	2.78	1.27	1.51	White	10	100
90988	250 MCM	3/0	1.09	0.594	0.46	2.78	1.27	1.51	Brown	10	100
90989	300 MCM	4/0	1.09	0.657	0.53	3.08	1.46	1.62	Brown	10	100
90990	350 MCM	250	1.09	0.704	0.57	3.08	1.46	1.62	Brown	10	100
90991	400 MCM	300	1.31	0.763	0.62	3.38	1.68	1.7	Pink	10	100
90992	500 MCM	350	1.31	0.842	0.68	3.38	1.68	1.7	Pink	10	100
90993	600 MCM	400	1.46	0.821	0.72	3.99	1.72	2.27	Yellow	3	30
90994	750 MCM	500	1.46	1.03	0.81	4.18	1.72	2.46	Yellow	3	30