


Section A-A

SR. NO	Part No.	Copper Wire Range Stranded	Copper Wire Range Solid	No. of Circuits	No. of Hole	All Dimensions are in mm.							MOUNTING HOLE POSITION
						A	B	C	ØD	F	G	Thread	
1	91152	4-14	8-14	4	6	49.28	11.17	7.87	6.25	7.92	5.00	1/4" x 28 UNF	1 & 6
2	91153	4-14	8-14	5	7	57.15	11.17	7.87	6.25	7.92	5.00	1/4" x 28 UNF	1 & 7
3	91154	4-14	8-14	6	8	65.00	11.17	7.87	6.25	7.92	5.00	1/4" x 28 UNF	1 & 8
4	91155	4-14	8-14	12	14	112.50	11.17	7.87	6.25	7.92	5.00	1/4" x 28 UNF	1 & 14
5	91156	4-14	8-14	13	15	120.40	11.17	7.87	6.25	7.92	5.00	1/4" x 28 UNF	3 & 13
6	91157	4-14	8-14	13	15	120.40	11.17	7.87	6.25	7.92	5.00	1/4" x 28 UNF	6 & 11
7	91158	4-14	8-14	190	190	1524.00	11.17	7.87	6.25	7.92	5.00	1/4" x 28 UNF	-
8	91159	2-14	8-14	3	5	50.80	12.70	9.65	8.10	10.08	7.00	5/16" x 28 UNF	1 & 5
9	91160	2-14	8-14	6	8	82.55	12.70	9.65	8.10	10.08	7.00	5/16" x 28 UNF	2 & 7

Note :-

- 1) Wire Size # 14 AWG to # 8 AWG - Torque - 2.3 Nm/20 in/lbs
- 2) Wire Size # 6 AWG to # 4 AWG - Torque - 3.5 Nm/31 in/lbs
- 3) Wire Size # 6 AWG to # 4 AWG - Torque - 5.1 Nm/45 in/lbs

Wire Size # 2 AWG & Onwards - Torque As per Standards

	NAME	DATE						
DRAWN		17/05/2014						
CHECKED		17/05/2014						
APPROVED		17/05/2014						
MATERIAL - Copper			Rev. No.	Details of Revision		Date	Drawn	Approved
TREATMENT -			 Morris Products Inc. TITLE - Copper Neutral Bar Cat# 91152 - 91160					
TOLERANCE - ±1.00								
SCALE - N.T.S.								
All dimensions are in mm.			Drawing No.-			Weight :-	Size :- A4	