



**Catalog Number** See Table  
**UPC Number** See Table  
**Description** Aluminum Long Barrel Compression Splice




**Features**

- Manufactured from High Strength High Conductivity Seamless Aluminum
- Electro-Tin Plated
- AL9CU Dual Rated for Copper or Aluminum Conductors
- Oxide Inhibitor filled/capped barrel
- Color coded & Marked with die size and crimp marks

**Wire Size** #8 Str thru 750 MCM

**Material** High Conductivity Seamless Aluminum  
**Material Treatment** Electro-Tin Plating  
**Stud Configuration** N/A



**Dimension Information**

See Table

**Specifications**

**Temperature Rating** 90° C  
**Voltage Rating** 35 KV  
**Flammability Rating** N/A  
**Amp Rating** To Conductor

**Packaging**  
**Box Qty** See table

**Certifications**  
**UL** UL486B AL9CU  
**cUL** Yes  
**RoHS** Yes

Cat No.	Wire Range	Color Code	Box Qty	Inside Diameter	Outside Diameter	Length
93208	8 Str.	Blue	50	.18(4.5)	.31(7.3)	1.50(38.1)
93210	6 Str.	Gray	50	.20(5.0)	.34(8.6)	1.63(41.4)
93212	4 Str.	Green	30	.25(6.3)	.44(11.1)	2.00(50.8)
93214	2 Str.	Pink	30	.31(7.8)	.53(13.4)	2.38(60.4)
93216	1 Str.	Gold	15	.35(8.8)	.53(13.4)	2.38(60.4)
93218	1/0 Str.	Tan	20	.39(9.9)	.63(16.0)	2.50(63.5)
93220	2/0 Str.	Olive	20	.44(11.1)	.69(17.5)	2.63(66.8)
93222	3/0 Str.	Ruby	15	.48(12.1)	.76(19.3)	2.88(73.1)
93224	4/0 Str.	White	10	.55(13.9)	.84(21.3)	3.13(79.5)
93226	250 MCM	Red	9	.59(14.9)	.92(23.3)	3.25(82.5)
93228	300 MCM	Blue	9	.65(16.5)	1.01(25.6)	3.25(82.5)
93230	350 MCM	Brown	6	.72(18.2)	1.12(28.4)	3.88(98.5)
93232	400 MCM	Green	6	.76(19.3)	1.19(30.2)	4.88(123.9)
93234	500 MCM	Pink	6	.84(21.3)	1.32(33.5)	5.00(127.0)
93236	600 MCM	Black	4	.92(23.3)	1.44(36.5)	5.13(130.3)
93238	750 MCM	Yellow	4	1.03(26.1)	1.60(40.6)	5.38(136.6)