



Catalog Number See Table
UPC Number
Description Insulation Piercing "Hot Tap" Connector
 1/0 - 750 MCM

Features

- Insulated Touch Proof Insulation Piercing Connector
- Double Head Shear Nut Ensures proper Torque during Installation
- Feed /Tap Configuration for Low Voltage Power Distribution Thru 600V
- Turco Spacer component maintains jaw opening for ease of installation
- Sealant Tank for watertight seal to environment after insulation piercing
- Jacket insert accomodates non-insulated cable constructions

General

Material: Tin Plated Copper Piercing Teeth
Insulation: Fiber reinforced Thermoplastic
Bolt: Gavanized Steel - Plastic Shear Head
Wire Range: 1/0 - 750 MCM

Dimension Information

See Table

Specifications

Temperature Rating 90°C
Voltage Rating 600
Flammability Rating N/A
Amp Rating To Conductor

Packaging

Box Qty See Table

Certifications

UL 486B Dual Rated CU9AL ANSI C119.4
cUL Yes
RoHS N/A

Cat No.	Number Of Bolts	Torque in inch lbs.	Bolt Head Size	Conductor Range		Dimensions in Inches			Box Qty
				Main AWG	Tap AWG	H	W	L	
96116	2	330	5/8"	350 - 1/0	350 - 1/0	5.4	3.1	5.0	4
96118	2	330	5/8"	500 - 2/0	4/0 - 4	5.4	3.1	5.0	4
96120	2	330	5/8"	500 - 4/0	350 - 1/0	5.4	3.0	5.0	4
96122	2	330	5/8"	750 - 250	500 - 250	5.6	3.6	5.7	4

www.morrisproducts.com

Morris Products 53 Carey Road, Queensbury, NY 12804