



Catalog Number See Table  
 UPC Number  
 Description Insulated Mechanical Connector  
 Multi-Cable Single Directional Entry  
 Black Insulation

Features	
-	Insulated Mechanical Connector - Blackr PVC Insulation
-	Multi-Tap Single Directional Conductor Entry
-	Aluminum Mechanical Connector
-	AL/CU Dual Rated
-	Gutter, Raceway, Enclosure Power Distribution Applications

General	
Material:	60601-T6 Plated Aluminum
Insulation:	Black Abrasion & Chemical Resistant PVC Insulation
Bolt:	See Table
Wire Range:	#14 - 750 MCM Prefilled Oxide Inhibitor

Dimension Information	
	See Table

Specifications	
Temperature Rating	49°F - 194°F
Voltage Rating	600
Flammability Rating	N/A
Amp Rating	To Conductor

Packaging	
Box Qty	See Table

Certifications			
UL	486B Dual Rated	CU9AL	ANSI C119.4
cUL	Yes		
RoHS	N/A		



Cat. No.	Wire Ports	Wire Range	Allen Hex	Length	Height	Box Qty
97513	3	4-14	Slotted	1.5	1.45	12
97514	4			1.92		12
97515	5			2.33		6
97516	6			2.75		4
97517	7			3.17		4
97518	8	2-14	Slotted	3.59	1.5	3
97519	3			1.6		6
97520	4			2.02		6
97521	5			2.43		4
97522	6			2.85		4
97523	7	1/0-14	3/16	3.27	1.85	3
97524	8			3.69		3
97525	3			1.9		8
97526	4			2.49		6
97527	5			3.08		4
97528	6	2/0-6	3/16	3.67	1.85	4
97529	7			4.26		3
97530	8			4.85		3
97533	3			1.9		8
97534	4			2.49		6
97535	5	3/0-6	1/4	3.08	1.99	4
97536	6			3.67		4
97537	7			4.26		3
97538	8			4.85		3
97579	3			2.1		6
97580	4	250-6	5/16	2.87	2.49	6
97581	5			3.64		4
97582	6			4.41		3
97583	7			5.18		3
97584	8			5.96		3
97543	3	350-6	5/16	2.4	2.64	6
97544	4			3.29		4
97545	5			4.17		4
97546	6			5.06		4
97547	7			5.94		3
97548	8	6.83	3			
97553	3	500-4	5/16	2.8	3.03	6
97554	4			3.85		4
97555	5			4.9		4
97556	6			5.95		3
97557	7			7		3
97558	8	8.06	3			
97585	3	600-250	5/16	3.18	3.11	4
97586	4			4.35		4
97587	5			5.53		4
97588	6			6.7		2
97589	7			7.87		2
97590	8	9.05	2			
97563	3	750-250	3/8	3.4	3.6	4
97564	4			4.68		4
97565	5			5.95		4
97566	6			7.23		2
97567	7			8.5		2
97568	8	9.78	2			
97573	3			3.6		4
97574	4			5.03		4
97575	5			6.45		4
97576	6			7.88		4
97577	7			9.3		2
97578	8	10.73	2			